

Technical Data Sheet

Auto291 Bumper Repair 1 Minute

PRODUCT DESCRIPTION

BONDLOC BUMPER REPAIR 1 Minute Adhesive 2K 1-1 PU fast adhesive, with around a 1 Minute cure time, allows for fast repair on damaged parts and also allows rebuilding of missing plastic, such as headlight, bumper and trim attachment tabs.

APPLICATIONS

Can drill or sander and overpaint within minutes. Suitable on all kinds of plastic, ABS, PVC, and metals, Not suitable on Polyethlene or Polyproplene.

USEFUL HINTS/NOTES

Benefits:

- Fast setting time with convenient 1:1 mix ratio
- Excellent adhesion to wide variety of surfaces such as aluminum, stainless steel, ABS, PVC, polyurethane, composites, thermoplastics, thermosetting plastics, wood, glass, concrete without any use of primer.

STORAGE

Store in a cool dry place.

TYPICAL CURED PROPERTIES

| · · · · · · · · · · · · · · · · · · · | | | |
|---------------------------------------|----------------------|---------------------|--|
| T-Peel Strength | 3,500 - 4,500 Pli | ASTM D1876 | |
| Tensile Elongation | 170% | ASTM D638 | |
| Shore Hardness | 70D | ASTM D 2240 | |
| Dielectric Strength | 350 | volts/ASTM D 149 | |
| Cure Shrinkage | 0.0020 in./in. | ASTM D 2566 | |
| Tear Resistance | 450 Pli | ASTM D 624 | |
| Tensile Strength | 2,850 psi | ASTM D 638 | |

TYPICAL PROPERTIES

| | Part A | Part B |
|------------------------------------|------------------------------------|--------|
| Colour | Beige | Black |
| Viscosity @25°C Brookfield, cps | 30,000 | 30,000 |
| Weight per Gallon | 11 | 11 |
| Mix Ratio | 1:1 | |
| Working Time | 60 – 100 seconds | |
| Fixture Time | 10 – 14 Minutes | |
| Functional Cure | 2 hours | |
| Full Cure | 24 Hours | |
| Service Temperature | -40°C to 121.1°C | |
| Coverage Per lb. | 94 sq. inch per lb @ $^{1}/_{4}$ " | |

LAP SHEAR STRENGTH (after 7 days @ 25°C)

| | , , |
|---------------------------|----------|
| ABS to ABS | 925 psi |
| Steel to Steel | 1975 psi |
| Glass to Glass | 4050 psi |
| SMC to SMC | 1280 psi |
| Aluminium to Aluminium | 2650 psi |
| Concrete to Concrete | 1945 psi |
| GBS to GBS | 2550 psi |
| Galvanised Metal to Metal | 2850 psi |

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS

PACKAGING FORMAT

25ml

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondioc are subject to terms and conditions set out in the contract. Bondioc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondioc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondioc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.





Technical Data Sheet

Auto291 Bumper Repair 1 Minute

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

