

# **Technical Data Sheet**

Auto72 Copper Anti-Seize

## PRODUCT DESCRIPTION

Bondloc Copper Anti-Seize lubricant is specially formulated to protect against seizure, even in extreme service conditions.

### **APPLICATIONS**

Bondloc Copper Anti-Seize makes assembling and dismantling of equipment easier and helps protect against rust, oxidation and other corrosion. Bondloc Copper Anti-Seize is resistant to temperatures up to 1093°C and is suitable for use on exhaust bolts, brake calliper bolts, steam valve threads etc. It can be used on threaded parts, reduces torque, prevents seizing and galling, give quick and easy breakout of threads, gaskets and packings.

### **INSTRUCTIONS FOR USE**

Clean mating surfaces for application. Note when grinding or wire brushing use a dust mask. Dust from cleaning threads may contain metal compounds. Inhalation may cause lung injury or other harm. Apply a thin coating to threads, flats, nuts and bolts. Assemble and wipe away any excess.

#### **TECHNICAL FEATURES**

Colour	Copper
Base	Bentone (infusible)
Odour	Mild petroleum
Solubility	Insoluble in water
Temperature Range	Any sub-zero -1093°C
Flash Point of Base Oil	228°C

#### **HEALTH & SAFETY**

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

# **PACKAGING FORMAT**

200ml (Power can), 500g

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondioc are subject to terms and conditions set out in the contract. Bondioc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondioc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondioc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

